

CP- VNR-3216-8P**16 Ch. 4K 8PoE Network Video Recorder****Main Features**

- 16 Channel IP Camera Input
- Support Ultra 265/H.265/H.264 Video Formats
- Support 4K Resolution Upto 12MP Resolution Recording
- 160Mbps Incoming/ 320Mbps Outgoing Bandwidth
- Support 2 SATA HDDs up to 8TB Each, 2 USB Ports, 8 PoE Ports
- Support HDMI and VGA simultaneous output
- Support Multi-brand network cameras
- Mobile Software: Android, iOS
- CMS Software: IVMS



CP- VNR-3216-8P

16 Ch. 4K 8PoE Network Video Recorder

Feature

Processor
IP Camera Input
Operating System
Two-way Talk
User Interface
Video Output
Compression
Recording Resolution
Video Recording
Video Display Split
Audio Input
Audio Output
Alarm Input
Alarm Output
Hard Disk
Playback
Max User Account
Interface Ports
Ethernet
PoE
Protocols
Power Supply
Power Consumption
Working Temp
Working Humidity
Dimensions
Weight

Specification

Dual-core embedded processor
16 channel
Embedded LINUX
1 channel, RCA
GUI
HDMI: 4K (3840x2160)/60Hz, 4K (3840x2160)/30Hz, 1920x1080p/60Hz, 1920x1080p/50Hz, 1600x1200/60Hz, 1280x1024/60Hz, 1280x720/60Hz, 1024x768/60Hz
VGA: 1920x1080p/60Hz, 1920x1080p/50Hz, 1600x1200/60Hz, 1280x1024/60Hz, 1280x720/60Hz, 1024x768/60Hz
Ultra 265, H.265, H.264
12MP/8MP/6MP/5MP/4MP/3MP/1080p/960p/720p/D1/2CIF/CIF
160Mbps
1/4/8/9/16
1 channel, RCA
1 channel, RCA
4 channel
1 channel
2 SATA ports, up to 8TB Each
16 Channel
128
2 USB Port (1 x USB 2.0, Rear panel: 1 x USB 3.0)
1 RJ-45 10M/100M/1000M self-adaptive Ethernet Interface
8 independent 100 Mbps PoE network interfaces
P2P, UPnP, NTP, DHCP, PPPoE, ONVIF (Profile S, Profile G, Profile T)
100 ~ 240 VAC , PoE: IEEE 802.3af/at
≤ 12 W (without HDD) , PoE: Max 30W for single port, Max 130W in total (16.25W for each)
-10°C ~ + 55°C (+14°F ~ +131°F)
≤ 90% RH (non-condensing)
380 mm x 315mm x 46 mm
≤ 2.42kg (without HDD)